



- 制作要求:
1. 框架使用80\*80\*5方管, 两侧扶手使用 $\phi 30 \times 3$ 圆管, 角铁规格40\*40\*3; 下叉车撑使用80\*40\*4矩形管
  2. 底板使用Q235B钢板, 厚度3;
  3. 小车全防护, 包括底板边缘防撞条、每层角铁橡胶垫、扶手护套等;
  4. 单侧单层承重不低于200kg;
  5. 脚轮为重型减震脚轮, 2只万向(带刹车), 2只定向, 每只设计承重不低于400kg;
  6. 支架喷涂蓝漆(可现场查看样品)

材质:

组合件

Continental

ContiTech

This drawing and the subject matter therein are the property of the Contitech(Shandong) Engineered Rubber Product Co., Ltd. and contains confidential and/or proprietary information and may not be copied, used or divulged without express written consent of Contitech(Shandong) Engineered Rubber Product Co., Ltd. All drawings and all parts or complete copies thereof will be returned or destroyed on request.

DRAWN BY:	2019/2/19	Q235	A4	FINISH
DATE:	MATERIAL:	SIZE:	FINISH:	
APPROVED BY:	1:15	283.02		
SCALE:	weight:			

DATE:	
缠绕合股锭子运输车	
JG-HG-04-00	
figure number :	